



FusionServer

2288 V8 Rack Server

Powerful performance | Solid Reliability and Security
Optimum Efficiency and Energy Saving



XFUSION INTERNATIONAL PTE. LTD.

Rack Server

FusionServer 2288 V8

Introduction



2288 V8 (front cable routing)



2288 V8 (24 drives)

The FusionServer 2288 V8 is a next-generation 2U2P rack server tailored to meet the demands of AI inference, cloud computing, virtualization, High-Performance Computing (HPC), graphics processing, VDI, and big data analytics.

Offering low power consumption, unmatched scalability, solid reliability, and ease of management and deployment, the 2288 V8 is an ideal choice for addressing massive workloads in industries such as Internet, telecom, government and enterprise, finance, and manufacturing.

Highlights



Supreme Computing

- **Power-Packed Performance:** 2 x Intel® Xeon® 6 6700P/6500P/6700E series processors
- **Exceptional Scalability:** Up to 16 x standard PCIe slots and 2 x OCP 3.0 slots, supporting PCIe 5.0 and cables routing from the front panel
- **High-speed flash memory and diverse configurations:** (1) Up to 20 x 3.5" drives*; (2) Up to 33 x 2.5" drives*; (3) Up to 36 x E3.s SSDs*



Outstanding Security

- **Enhanced Maintenance Efficiency:** Quick, precise PCIe link fault diagnosis, boosting efficiency by 50%
- **Reduced System Downtime:** Industry-exclusive AI memory self-healing, with precise memory link diagnosis, cutting downtime by 66%



Optimal Energy Efficiency

- **Dynamic Energy Management:** Intelligent, non-disruptive tuning based on workloads, achieving peak energy efficiency without rebooting
- **Industry-Leading Power Supply:** 97% power conversion efficiency, driven by three core innovations, setting the benchmark

*Configuration details are subject to the technical white paper

Rack Server

FusionServer 2288 V8

Technical Specifications

Form Factor	2U Rack Server
Processor	2 x Intel® Xeon®6 6700P/6500P/6700E Scalable processors with TDP 350W per processor
Memory	32 x memory slots available for DDR5 DIMMs at up to 6400 MT/s or MRDIMMs at up to 8000 MT/s
Local Storage	Hot-swappable drives configurations: - Up to 20 x 3.5" drives* - Up to 33 x 2.5" drives* - Up to 36 x E3.s SSDs* Flash storage: 2 x M.2 SSDs, hardware RAID, and hot swap
RAID	RAID 0, 1, 10, 1E, 5, 50, 6, or 60; supercapacitors for cache data protection from power failures; RAID level migration, drive roaming, self-diagnosis, and remote web-based configuration
Network	Multiple network expansion capabilities; 2 x FlexIO card slots dedicated for OCP 3.0 NICs, which can be configured as required; supporting hot swap and PCIe 5.0
PCIe Expansion	Up to 16 x standard PCIe slots and 2 x OCP 3.0 slots, supporting PCIe 5.0 and cables routing from the front panel
GPU Card	4 x dual-width GPU cards*
Fan	4 or 6 x hot-swappable counter-rotating fans in N+1 redundancy
PSU	900 W/1200 W/1500 W/2000 W/3000 W Platinum/Titanium hot-swappable PSUs in 1+1 redundancy
Management	The iBMC chip integrates one dedicated management GE network port, providing comprehensive management features such as fault diagnosis, automatic O&M, and hardware security hardening. - The iBMC supports standard interfaces such as Redfish, SNMP, and IPMI 2.0, provides a remote management user interface based on HTML5/VNC KVM; supports out-of-band management functions such as monitoring, diagnosis, configuration, Agentless, and remote control for simplified management - It is optional to configure the FusionDirector management software that provides advanced management features such as five intelligent technologies, enabling intelligent, automatic, visualized, and refined management throughout the lifecycle
OS	Microsoft Windows Server, SUSE Linux Enterprise Server, VMware ESXi, Red Hat Enterprise Linux, Oracle, Ubuntu, and openEuler
Security	Power-on password, administrator password, Trusted Platform Module (TPM) 2.0, security bezel, secure boot, and chassis intrusion detection
Operating Temperature	5°C to 45°C (41°F to 113°F), compliant with ASHRAE Classes A1/A2/A3/A4
Installation Suite	L-shaped guide rails, adjustable guide rails, and holding rails
Dimensions (H x W x D)	86.1 mm x 447 mm x 798 mm (3.39 in. x 17.60 in. x 31.42 in.)

*Configuration details are subject to the technical white paper



Copyright ©xFusion International Pte. Ltd. 2026. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of xFusion International Pte. Ltd.

Trademarks and Permissions

xFUSION and other xFusion trademarks are trademarks of xFusion International Pte. Ltd. All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

In this document, "xFusion" is used to refer to "xFusion International Pte. Ltd." for concise description and easy understanding, which does not mean that "xFusion" may have any other meaning. Any "xFusion" mentioned or described hereof may not be understood as any meaning other than "xFusion International Pte. Ltd.", and xFusion International Pte. Ltd. shall not bear any liability resulting from the use of "xFusion".

The purchased products, services and features are stipulated by the contract made between xFusion and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.